

STONE 832

TECHNICAL DATA LAMINATE

Classification	Norm	Tarkett Value		
Product type	EN 13329	Laminate floor covering		
Class of use	EN 13329	32		
HDF core board density	EN 323	900 kg/m ³ (± 20 kg/m ³)		
Locking system		ANGLE LOCK		
Technical characteristics				
Format		Classic		
Dimensions		1292 x 193 mm		
Complete thickness		8 mm		
Bevel		0V		
Performance for CE marking				
Declaration of Performance	EN 14041	0132-0078-DoP-2019-06		
Reaction to fire	EN 14041	Cfl-s1		
Slip resistance	EN 14041	DS		
Electrostatical propensity	EN 14041	< 2 kV		
Thermal resistance (in m ² K/W)	EN 14041	≤ 0,15 m ² K/W		
Content of Pentachlorophenol	EN 14041	< 5 ppm		
Formaldehyde emission	EN 14041	E1		
Technical performance				
Abrasion resistance	EN 13329, annex E	AC4 (IP ≥ 4000)		
Impact resistance	EN 13329, annex H	Big ball: ≥ 750 mm Small ball: ≥ 12 N		
Resistance to staining	EN 438	Group 1 + 2: level 5 Group 3: level 4		
Effect of furniture leg	EN 424	No damage shall be visible, when tested with foot Type 0 artefact		
Effect of castor chair	EN 425 (Type W)	No change in appearance or damage		
Thickness swelling	ISO 24336	≤ 18 %		
Tolerance top layer	EN 13329	Length ± 0,5 mm Width ± 0,1 mm Thickness ± 0,5 mm		
Light fastness	EN 13329	Grey scale ≥ level 4 (EN:20105-A02)		
Static indentation by constant pressure	EN ISO 24343-1	< 0,05		
Surface soundness	EN 13329, annex D	≥ 1,25 N/mm ²		
Thermal resistance	EN 12667	0,07 m ² K/W		
Sustainability & environment				
PEFC certification		Yes		
French VOC rating		A+		
Emission class for building material		M1		
Carb 2 compliance		Yes		
Logistics information				
8 planks/box	1,99 m ² /box	7,24 kg/m ²	60 boxes/pallet	119,70 m ² /pallet

The above information is subject to modification for the benefit of further improvement (09/2019)



EN 13329

